

Leo Minor LED Surgical Light Ceiling - Quick Installation Guide

1.0 Scope of Delivery Included:



1x Transformer box with light wiring harness and power cable.



1x Leo Minor Light Head Assembly



1x Ceiling Mount



1x Ceiling Arm



1x Ceiling Down Tube with light wiring harness.



(from left to right)

- 1x Down Tube Washer
- 1x Down Tube Safety Washer
- 2x Down Tube Locking Rings



2x Down Tube Mounting Pins 2x Down Tube Cotter pins



1x Leo Minor Head Yoke Brass Coupler (2 halves)



1x Ceiling Cover 1x Retailing Ring

2.0 Installing the Mount

2.1 Load Data


Bending moment M _B	_{max.} 210 Nm
Vertical weight forces F _G	_{max.} 205 N

- 1x load only. Regional safety factors to be considered.
- Maximum device load is assumed and included.

2.2 Installing the Ceiling Mount


"Secure ceiling mount to the ceiling using the mount holes provided, and the load data listed in Section 2.1. <u>Mounting hardware</u> not included.

Insure 2"(50mm)- 4"(100mm) of clearance is present above the ceiling mount.




2.3 Installing the Down Tube

- ^aPull the lamp wiring harness from the down ceiling tube through the mounting.
- Insert down ceiling tube into the mounting.
- Secure the down ceiling tube with the 2 mounting pins and 2 cotter pins.



- ^oSecurely tighten the 4 Allen screws in the mounting.
- ^oDown ceiling tube and the mounting must be plumb or leveled.




^oSlide cover and retaining ring onto ceiling down tube.




2.4 Installing the Ceiling Arm

Gently pry the two halves of the cover apart and set aside.



^aRemove 2 screws from receptacle mount.






^oGently pull the receptacle out of the arm downward. (this will ensure clearance of installing the washer set onto the down ceiling tube In the next step)





- ^aFirst install washer (1), then safety washer (2), followed by two locking rings (3) onto the ceiling down tube.
- ^eEnsure tooth on safety washer aligns with the hole in the ceiling tube (4).




- ^aReplace receptacle into mount.
- Reinstall 2 screws, do not over tighten.
- Gently replace covers and snap together.



2.4 Installing Leo Minor LED light Head

^oLoosen set screw on arm end sleeve and rotate 180° to align with key and key hole.




^oGently pry key from hole and pull end cap off of arm.





- Place the 2 halve brass coupler onto yoke with flange side toward the head.
- ^oPlace a small amount of grease (supplied) on the inside and outside of coupler.



- ^oSlide head with brass coupler into the arm.
- ^aReplace key into key hole.




Rotate arm end sleeve 180° and tighten set screw.




2.5 Installing Transformer Box

- ⁿMount transformer box in a suitable location.
- ^aPlug connector from down tube with the connector from the transformer box.



^oJoin grounding wires from the transformer Box, down tube and ceiling cover onto the common grounding bolt located on the ceiling mount.



- ^aAdjust ceiling cover to fit over ceiling mount.
- Plug transformer power cable into 120-240Vac/50-60hz power receptacle.

END

Version 2.0 October 2015